Filter Separators Model 9003 Model 9004 2.63" 67r 1/4 이징이 6.23" 000 Model 9001 & 9032 Model 9002 3.74" 95mm 3/8 NPT or 1/2 NPT 3/4 NPT 11.02 Model 9066

EXAIR's Filter Separators remove water, dirt and rust from your compressed air system. They prevent these contaminants from plugging or damaging the compressed air products. A Filter Separator should be installed prior to an Oil Removal Filter, pressure regulator or valve.

The Model 9003 Manual Drain Filter has a polycarbonate bowl and a 20 micron filter element. A manual drain is used to empty the filter. Model 9001, 9002, 9004, 9032, and 9066 Automatic Drain Filter Separators have a metal bowl and a 5 micron filter element (Model 9004 has a polycarbonate bowl with a metal guard). An internal float automatically activates the drain to remove liquid condensate when the bowl becomes full.


Model# Description Max Pres. Max Temp. 9003 Manual Drain Filter Separator, 1/4 NPT, 27 SCFM (765 SLPM) 150 PSIG 125°F (52°C 9004 Automatic Drain Filter Separator, 1/4 NPT, 43 SCFM (1,218 SLPM) 150 PSIG 125°F (52°C) 10.38 9001 Automatic Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM) 175 PSIG 120°F (49°C) 9032 Automatic Drain Filter Separator, 1/2 NPT, 90 SCFM (2,549 SLPM) 120°F (49°C) Automatic Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM) 9002 175 PSIG 120°F (49°C) 9066 Automatic Drain Filter Separator, 1-1/4 NPT, 400 SCFM (11,327 SLPM) 175 PSIG 120°F (49°C)

Oil Removal Filters Model 9027 Model 9010 12 Imm 11-1/2 NPT 17 Sem Model 9010 2.475 13 3 mm 1-1-1/2 NPT 1-1-1/4 NPT ADAPTES NCLUDED 14.5° 368mm Model 9005 2.61° 66mm

EXAIR's Model 9027, 9005, 9006, and 9010 Oil Removal Filters remove oil and solid particulate that is typical in many compressed air systems.

A 0.03 micron element is used to trap submicron particles. An internal float automatically activates the drain when full.

Model #	Description	Max Pres.	Max Temp.
9027	Oil Removal Filter, 1/4 NPT, 24 SCFM (680 SLPM)	175 PSIG	120°F (49°C)
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	175 PSIG	120°F (49°C)
9006	Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM)	175 PSIG	120°F (49°C)
9010	Oil Removal Filter, 1-1/2 NPT, 130-310 SCFM (3,679-8,773 SLPM)	175 PSIG	120°F (49°C)



Model #	Description
900395	Mounting Bracket for Model 9003
900396	Mounting Bracket for Model 9001, 9004, 9005, 9027, and 9032
900397	Mounting Bracket for Model 9002



Pressure Regulators

EXAIR's Model 9008, 9033, 9009 and 9067 Pressure Regulators permit easy selection of the operating pressure. A pressure gauge is included.

Model 9008



Model 9033




Model 9009



Model 9011




Model 9067



Model #	Description	Max Pres.	Max Temp.
9008	Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM)	250 PSIG	120°F (49°C)
9033	Pressure Regulator with Gauge, 1/2 NPT, 100 SCFM (2,832 SLPM)	250 PSIG	120°F (49°C)
9009	Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM)	250 PSIG	120°F (49°C)
9067	Pressure Regulator with Gauge, 1-1/4 NPT, 700 SCFM (19,822 SLPM)	250 PSIG	120°F (49°C)
9011	Pressure Gauge Only, 1/4 NPT, 0-160 PSI (0-11 BAR)	250 PSIG	120°F (49°C)

Pressure Regulator Mtg Brackets



This optional mounting bracket fits Models 9008, 9033 and 9009 Pressure Regulators and includes a locking ring.

Model # Description

900398 Mounting Bracket for Model 9008, 9033 and 9009

Mounting and Coupling Kits



	Model #	Description	
	9046	Mounting and Coupling Kit for Model 9001 Filter/Model 9008 Regulator and Model 9032 Filter/Model 9033 Regulator	
Г	9047	Mounting and Coupling Kit for Model 9002 Filter/Model 9009 Regulator	
	9048	Mounting and Coupling Kit for Model 9004 Filter/Model 9005 Oil Removal Filter	

Coupling Kits



EXAIR Corporation

EXAIR's Coupling Kits are interlocking slides that couple the modular filters and pressure regulators together.

Model #	Description	
900394	Fits auto drain filters and regulators with 1/4 NPT, 3/8 NPT and 1/2 NPT threads	
900552	Fits auto drain filters and regulators with 3/4 NPT threads	













