



Light Duty Line Vac™

An effective way to convey small volumes of material over short distances!



What Is The Light Duty Line Vac?

EXAIR's Light Duty Line Vac is the ideal way to convey small volumes of materials over short distances. Like the Line Vac shown on page 141, the Light Duty Line Vac converts an ordinary hose or tube into a conveyor for scrap, trim and bulk materials.

Why The Light Duty Line Vac?

When lower throughputs at short distances are desired, the Light Duty Line Vac is a good choice. This simplified design utilizes a two-part threaded construction to provide effective conveying at a lower cost. Air consumption is reduced to a volume appropriate for moving small volumes of material at short distances. Conveying rates are easy to control by regulating the compressed air supply pressure.

The Light Duty Line Vac features inlet and outlet diameters common to hose and tube sizes. Eight sizes for diameters from 3/4" to 6" (19 to 152mm) are available. Standard construction is aluminum. (For corrosion resistant stainless steel models that are suitable for high temperature and food service, please see Line Vac models on page 146.) No moving parts or electricity assures maintenance free operation. (If higher conveying rates or mounting brackets are desired, see the Line Vac models on page 146.)





The low cost Model 130200 2" (51mm) Light Duty Line Vac conveys fibers to fill pillows, stuffed animals, diapers, etc.

Applications

- Hopper loading
- Fiber tensioning
- Material conveying
- · Waste/trim removal
- Chip removal
- Part transfer
- Filling operations

Advantages

- Compact
- Quiet
- No moving parts
- Fits standard hose or tube
- Aluminum
- Eight sizes
- Moderate throughput capability



A Model 130125 1-1/4" (32mm) Light Duty Line Vac can fill or empty the packing peanuts from shipping cartons.









Light Duty Line Vacs are available in eight sizes for diameters from 3/4" to 6" (19 to 152mm).

| Light Duty Line Vac Dimensions | | | | | | | | |
|--------------------------------|----|------|------|------|------|------|------|-----|
| Model # | | Α | В | c | D | E | F | G |
| 130075 | in | 0.75 | 0.50 | 1.88 | 4.53 | 2.31 | 1.06 | 1/4 |
| | mm | 19 | 13 | 48 | 115 | 59 | 27 | NPT |
| 130100 | in | 1 | 0.75 | 2.13 | 4.53 | 2.41 | 1.06 | 1/4 |
| | mm | 25 | 19 | 54 | 115 | 61 | 27 | NPT |
| 130125 | in | 1.25 | 1 | 2.38 | 4.53 | 2.41 | 1.06 | 1/4 |
| | mm | 32 | 25 | 60 | 115 | 61 | 27 | NPT |
| 130150 | in | 1.50 | 1.25 | 2.75 | 4.63 | 2.41 | 1.06 | 3/8 |
| | mm | 38 | 32 | 70 | 117 | 61 | 27 | NPT |
| 130200 | in | 2 | 1.75 | 3.25 | 4.66 | 2.47 | 1.06 | 3/8 |
| | mm | 51 | 45 | 83 | 118 | 63 | 27 | NPT |
| 130300 | in | 3 | 2.75 | 4.25 | 5.06 | 2.75 | 1.06 | 3/8 |
| | mm | 76 | 70 | 108 | 129 | 70 | 27 | NPT |
| 130400 | in | 4 | 3.75 | 5.25 | 5.06 | 2.75 | 1.06 | 1/2 |
| | mm | 102 | 95 | 133 | 129 | 70 | 27 | NPT |
| 130600 | in | 6 | 5.75 | 7.38 | 5.56 | 2.88 | 1.06 | 1/2 |
| | mm | 152 | 146 | 187 | 141 | 73 | 27 | NPT |

Light Duty Line Vac Systems

Light Duty Line Vac Models

Light Duty Line Vac Only

Light Duty Line Vac Kits - include the Light Duty Line Vac, filter separator and pressure regulator (with coupler).

| Inlet/Outlet Diameter | Light Duty Line Vac Only Model | Light Duty Line Vac Kit Model | |
|--------------------------|--------------------------------------|-------------------------------------|--|
| 3/4" (19mm) | 130075 | 132075 | |
| 1" (25mm) | 130100 | 132100 | |
| 1-1/4" (32mm) | 130125 | 132125 | |
| 1-1/2" (38mm) | 130150 | 132150 | |
| 2" (51mm) | 130200 | 132200 | |
| 3" (76mm) | 130300 | 132300 | |
| 4" (102mm) | 130400 | 132400 | |
| 6" (152mm) | 130600 | 132600 | |



Accessories

| Model # | Description |
|---------|--|
| 9001 | Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM) |
| 9002 | Auto Drain Filter Separator, 3/4 NPT, 220 SCFM (6,230 SLPM) |
| 9005 | Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM) |
| 9006 | Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM) |
| 9008 | Pressure Regulator with Gauge, 1/4 NPT, 50 SCFM (1,416 SLPM) |
| 9009 | Pressure Regulator with Gauge, 3/4 NPT, 220 SCFM (6,230 SLPM) |

Hose is available in 10', 20', 30', 40' and 50' lengths. Select the hose model number (diameter) and indicate the length with a dash. Example: A Model 6931-20 is 1" ID Hose x 20' long.

| 6930- | Hose 3/4" ID |
|-------|----------------|
| 6931- | Hose 1" ID |
| 6932- | Hose 1-1/4" ID |
| 6933- | Hose 1-1/2" ID |
| 6934- | Hose 2" ID |
| 6936- | Hose 3" ID |



Kits include a Light Duty Line Vac, filter separator and pressure regulator (with coupler).

DOWNLOAD drawings at EXAIR.com





Light Duty Performance

| 80 PSIG (5.5 BAR) | Air Consumption | | | |
|----------------------|-----------------|-------|--|--|
| Model # | SCFM | SLPM | | |
| 130075 | 7.30 | 207 | | |
| 130100 | 10.70 | 303 | | |
| 130125 | 14.70 | 501 | | |
| 130150 | 20 | 566 | | |
| 130200 | 27.50 | 778 | | |
| 130300 | 45 | 1,274 | | |
| 130400 | 58.50 | 1,656 | | |
| 130600 | 80.20 | 2.270 | | |



PVC hose is available in lengths up to 50' (15.2m) and diameters up to 3" (76mm).





