

























Features Quick Reference Sheet - OIS CP Range




 QRS 3-7.5
 
 QRSM 10
 
 QRS 10-15
 QRSM 20
 CPVSd 10-20
 
 QRS 20-30
 CPVS 20-30
 
 CPBg 35-50
 CPVSd 35-50
 
 CPC(-G)40-60
 CPVS 40-60
 
 CPD(-G)75-100
 CPVS 75-95
 
 CPE 100-150
 CPF 175
 CPVS 100-150
 
 CPF 200
 CPVS 250
 
 CPF 270-340
 
 CPG 350
 
 CPG 450-500

Air End	C40 	C55 	C55* 	C77 	C80 	C90 	C111 	C146 	S2L 	C190 	C242 	2 x C242 
HP	3-7.5	10	10-20	20-30	35-50	40-60	75-100	100-175	200-240	270-340	350	450-500
Flow (ACFM) @ 125 PSI	8.5-21.2 (@150 PSI)	33 (@150 PSI)	9-78	80-117	154-205	174-261	305-402	439-752	911 173-1071 (VSD)	1112-1306	1811	1988-2204
Control Type												
Press-switch	✓	✓	-	-	-	-	-	-	-	-	-	-
ES3000	-	-	-	✓	-	-	-	-	-	-	-	-
ES4000 Basic	-	-	✓	-	-	-	-	-	-	-	-	-
ES4000 Standard	-	-	-	-	✓	✓ (Belt)	✓ (Belt)	-	-	-	-	-
ES4000 Advanced	-	-	✓(VSD)	-	✓ (VSD)	✓ (Gear)	✓ (Gear)	✓	-	✓	✓	-
Airlogic	-	-	-	-	-	-	-	✓ (175)	✓	-	-	✓
Oil Type												
Rotair	✓*	✓*	✓*	✓*	✓*	-	-	-	-	-	-	-
Rotair Xtra	-	-	✓(VSD)	-	✓ (VSD)	✓	✓	✓	✓	✓	✓	✓
Rotair Foodgrade	OPTIONAL											
Direct Drive	-	-	✓	-	✓ (VSD)	-	-	-	-	-	-	-
Belt Driven	✓	✓	✓(Fixed)	✓	-	✓	✓	-	-	-	-	-
Gear Driven	-	-	-	-	✓	✓(-G & VSD)	✓(-G & VSD)	✓	✓	✓	✓	✓
Integrated Dryer Option	✓	✓	✓ (& WSD)	✓ (& Filter)	✓ (& Filter)	✓(-G; & WSD)	-	-	-	-	-	-
Water Cooled	-	-	-	-	-	-	✓	✓	-	✓	✓	✓
After Cooler	-	-	✓(VSD)	✓	✓	✓	✓	✓	✓	✓	✓	✓
VSD	-	-	✓	✓	✓	✓	✓	✓	✓	-	-	-
Tank Mount	✓	✓	✓	✓	-	-	-	-	-	-	-	-
Inverter Brand	-	-	Danfoss	Vacon	Danfoss	Vacon	Imperium	Imperium	Vacon	-	-	-

*Use of Rotair Plus recommended at first oil change.