

#### **Oil/Water Separators**

Oil/Water Separation for Cleaner Condensate Discharge

# Posi-Zorb



Designed to handle system-upset conditions and a variety of oils. Capable of 24 hour continuous operation. No electricity required.

#### Features

- Constructed of all non-corrosive materials
- Proprietary media filter
- Non-clogging filter design
- Pneumatically operated pump

#### Only 2 moving parts

Self-contained filter modules

### Benefits

Easily maintained
Runs clog free - extended service life
Uninterrupted service
Ensures uninterrupted filtration
from condensate streams
Dependable service
Ease of installation and replacement –
no messy bags to dispose of



The Posi-Zorb is available with three sizes of self-contained filter modules

## How it Works

The Posi-Zorb is designed specifically to ensure uninterrupted service and to extend the life of the filter module. The filter module contains proprietary media that selectively removes emulsified oils and may hold up to four times the amount of oil compared to standard activated carbon. The unit continues to function even in the event of upset conditions. The system only operates when the level of condensate rises. The unit also enables easy disposal. Once the filter media is saturated, the modules are simple to replace and there are no messy bags to handle. The modules are entirely self-contained and permit ease of installation and replacement.

#### Dimensions

#### Max. CFM Capacity\* Model 90°F/90%RH Height Depth Width Dry Weight Lbs. PZD-01-15 250 38" 23" 28" 90 PZD-01-30 500 38" 23" 28" 200 PZD-01-55 1000 38" 23" 28" 400

\* The maximum CFM capacity is based on polyglycol. Ratings listed may be increased by 25% if a refrigerated air dryer is not used. Not recommended for silicone-based lubricants.

A PZM Filter Module could last 12 months in a Rotary Screw application. However, filter life may be less due to lubricant, compressor type, and maintenance.

Please contact your local Distributor or the Factory for proper sizing when using other types of lubricants and/or compressors.

Visit **airsyspro.com/selector-guide** to use our Condensate Separator Guide



AIRTEC GLOBAL LLC 1100 NW Loop 410 Ste. 764 San Antonio, TX 78213 Phone: (210) 366-8805 Email: support@airtec.global http://airtec.global